

KENMORE GAS WATER HEATERS - 2009

BEST

KENMORE POWER MISER 12 Gas Water Heaters

12-Year Limited Warranty On Tank And Parts • 1-Year Labour Warranty

- Glass-lined steel tank with two large anode rods for corrosion protection
- Self-Cleaning, Roto-Swirl™ cold water inlet tube... swirls incoming water to help prevent sediment build-up
- More gallons per hour recovery than Power Miser 9 series
- Easy-to-light, Piezo ignition system
- 2" Energy-Efficient, CFC-free foam insulation
- Factory installed temperature / pressure relief valve
- **ENERGY STAR® Qualified models available**

ITEM NUMBER	ENERGY STAR QUALIFIED	TANK CAPACITY		TYPE GAS	BTU/HR. INPUT	U.S. GAL./HR. RECOVERY @ 90°F RISE	DIMENSIONS IN INCHES			VENT SIZE	INSULATION R-FACTOR
		U.S. GALLONS	IMPERIAL GALLON				DIAMETER	VENT OUTLET HEIGHT	JACKET HEIGHT		
73930	Yes	40 Tall	33	Natural	40,000	40.9	20.0"	62.0"	58.25"	3" or 4"	R-16
73931	Yes	50 Tall	42	Natural	40,000	40.9	22.0"	61.0"	57.25"	3" or 4"	R-16
73830	No	40 Tall	33	Natural	50,000	51.2	20.0"	62.5"	58.25"	4"	R-16
73431	No	50 Tall	42	Natural	50,000	51.2	22.0"	61.5"	56.5"	4"	R-16
73831**	No	50 Tall	42	Natural	50,000	51.2	22.0"	61.5"	57.25"	4"	R-16

BETTER

KENMORE POWER MISER 9 Gas Water Heaters

9-Year Limited Warranty on Tanks and Parts • 1-Year Labour Warranty

- Glass-lined steel tank with two large anode rods for corrosion protection
- Self-Cleaning, Roto-Swirl™ cold water inlet tube... swirls incoming water to help prevent sediment build-up
- Easy-to-light, Piezo ignition system
- Energy-Efficient, CFC-free foam insulation
- Propane gas models available in 40 and 50 U.S. gallon sizes
- Factory installed temperature / pressure relief valve
- **ENERGY STAR Qualified models available**

ITEM NUMBER	ENERGY STAR QUALIFIED	TANK CAPACITY		TYPE GAS	BTU/HR. INPUT	U.S. GAL./HR. RECOVERY @ 90°F RISE	DIMENSIONS IN INCHES			VENT SIZE	INSULATION R-FACTOR
		U.S. GALLONS	IMPERIAL GALLON				DIAMETER	VENT OUTLET HEIGHT	JACKET HEIGHT		
73910**	Yes	40 Short	33	Natural	40,000	40.9	22.0"	51.5"	47.75"	3" or 4"	R-16
73911	Yes	40 Tall	33	Natural	40,000	40.9	20.0"	62.0"	58.25"	3" or 4"	R-16
73912	Yes	50 Tall	42	Natural	40,000	40.9	22.0"	61.0"	57.25"	3" or 4"	R-16
73810	No	40 Short	33	Natural	40,000	40.9	20.0"	51.5"	47.75"	3" or 4"	R-8
73811	No	40 Tall	33	Natural	40,000	40.9	18.0"	62.0"	58.25"	3" or 4"	R-8
73814	No	40 Short	33	Propane	36,000	36.9	20.0"	51.5"	47.75"	3" or 4"	R-8
73016	No	50 Short	42	Natural	45,000	47.3	24.0"	53.25"	48.75"	4"	R-16
73616**	No	50 Short	42	Natural	45,000	46.1	24.0"	53.25"	49.0"	4"	R-16
73017	No	50 Short	42	Propane	42,500	44.6	24.0"	53.25"	48.75"	4"	R-16
73617**	No	50 Short	42	Propane	42,500	43.5	24.0"	53.25"	49.0"	4"	R-16
73716	No	65	54	Natural	65,000	67.0	24.0"	64.0"	60.25"	4"	R-16
73916**	No	65	54	Natural	65,000	66.5	24.0"	64.75"	60.5"	4"	R-16

BETTER

KENMORE POWER MISER Power Vent Gas Water Heaters

9-Year Limited Warranty on tank, 4-Year Limited Warranty on parts; 1-Year Labour Warranty

- Energy-saving, Hot Surface Ignition System... No standing pilot.
- Uses PVC pipe for venting system
- No chimney required... Vents through outside wall or roof
- Requires 120-Volt, grounded power supply
- **ENERGY STAR Qualified**

ITEM NUMBER	ENERGY STAR QUALIFIED	TANK CAPACITY		TYPE GAS	BTU/HR. INPUT	U.S. GAL./HR. RECOVERY @ 90°F RISE	DIMENSIONS IN INCHES			VENT SIZE	INSULATION R-FACTOR
		U.S. GALLONS	IMPERIAL GALLON				DIAMETER	VENT OUTLET HEIGHT	JACKET HEIGHT		
73425	Yes	50	42	Natural	40,000	44.2	20.0"	65"	56.75"	2", 3" or 4"	R-8
73426	Yes	50	42	Natural	50,000	53.2	22.0"	65"	56.75"	2", 3" or 4"	R-16

GOOD

KENMORE POWER MISER 6 Gas Water Heaters

6-Year Limited Warranty On Tank And Parts • 1-Year Labour Warranty

- Glass-lined steel tank with two large anode rods for corrosion protection
- Easy-to-light, Piezo ignition system
- 2" Energy-Efficient, CFC-free foam insulation
- Factory installed temperature / pressure relief valve
- **ENERGY STAR Qualified models available**

ITEM NUMBER	ENERGY STAR QUALIFIED	TANK CAPACITY		TYPE GAS	BTU/HR. INPUT	U.S. GAL./HR. RECOVERY @ 90°F RISE	DIMENSIONS IN INCHES			VENT SIZE	INSULATION R-FACTOR
		U.S. GALLONS	IMPERIAL GALLON				DIAMETER	VENT OUTLET HEIGHT	JACKET HEIGHT		
73900**	Yes	40 Short	33	Natural	40,000	40.9	22.0"	51.5"	47.75"	3" or 4"	R-16
73800	No	40 Short	33	Natural	40,000	40.9	20.0"	51.5"	47.75"	3" or 4"	R-8
73801	No	40 Tall	33	Natural	40,000	40.9	18.0"	62.0"	58.25"	3" or 4"	R-8

Note: For installation of gas water heaters at elevations above 7,700 feet, contact the local gas utility for necessary modifications.

Dimensions and product specifications are subject to change without notice.

Gas water heaters shown are not certified for use in mobile homes.

All models shown comply with the latest efficiency requirements of NRCAN.

** Item Numbers shown in **BOLD** will not be available until the 2nd Quarter of 2009

KENMORE ELECTRIC WATER HEATERS - 2009

BEST

KENMORE POWER MISER 12 Electric Water Heaters 12-Year Limited Warranty On Tank And Parts • 1-Year Labour Warranty

- Glass-lined steel tank with two large anode rods for corrosion protection
- Self-Cleaning, Roto-Swirl™ cold water inlet tube... swirls incoming water to help prevent sediment build-up
- Super Limeguard, stainless steel heating elements
- 3" Energy-Efficient, CFC-free foam insulation
- Dual-Watt lower element...converts from 3800 watts to 5500 watts... for use with either 20 amp or 30 amp fuses or circuit breakers
- Factory installed temperature / pressure relief valve

ITEM NUMBER	TANK CAPACITY		WATTAGE AT 240 VOLTS	MINIMUM FUSE REQUIRED	MINIMUM WIRE SIZE	U.S. GAL./HR. RECOVERY @ 90°F RISE		DIMENSIONS IN INCHES		INSULATION R-FACTOR
	LITRES	IMPERIAL GALLON				LITRES PER HOUR	IMPERIAL GALLON PER HOUR	DIAMETER	HEIGHT	
73432	273	60.0	3800	20 amp	12 ga.	65.5	14.4	26"	62"	R-24
			5500	30 amp	10 ga.	94.8	20.9			
73433	170	37.5	3800	20 amp	12 ga.	65.5	14.4	24"	50"	R-24
			5500	30 amp	10 ga.	94.8	20.9			

BETTER

KENMORE POWER MISER 9 Electric Water Heaters 9-Year Limited Warranty on Tanks and Parts • 1-Year Labour Warranty

- Glass-lined steel tank with two anode rods for corrosion protection
- Self-Cleaning, Roto-Swirl™ cold water inlet tube...swirls incoming water to help prevent sediment build-up
- Limeguard, Zinc-coated, Copper heating elements
- 2.5" Energy-Efficient, CFC-free foam insulation Propane gas models available in 40 and 50 U.S. gallon sizes
- Dual-Watt lower element...converts from 3800 watts to 5500 watts...for use with either 20 amp or 30 amp fuses or circuit breakers
- Factory installed temperature / pressure relief valve

ITEM NUMBER	TANK CAPACITY		WATTAGE AT 240 VOLTS	MINIMUM FUSE REQUIRED	MINIMUM WIRE SIZE	U.S. GAL./HR. RECOVERY @ 90°F RISE		DIMENSIONS IN INCHES		INSULATION R-FACTOR
	LITRES	IMPERIAL GALLON				LITRES PER HOUR	IMPERIAL GALLON PER HOUR	DIAMETER	HEIGHT	
73416	225	49.4	3800	20 amp	12 ga.	65.5	14.4	23"	61"	R-20
			5500	30 amp	10 ga.	94.8	20.9			
73417	273	60.0	3800	20 amp	12 ga.	65.5	14.4	25"	61.5"	R-20
			5500	30 amp	10 ga.	94.8	20.9			
73418	187	41.2	3000	15 amp	14 ga.	51.7	11.4	21.5"	61"	R-20
73419	187	41.2	3800	20 amp	12 ga.	65.5	14.4	21.5"	61"	R-20
			5500	30 amp	10 ga.	94.8	20.9			

GOOD

KENMORE POWER MISER 6 Electric Water Heaters 6-Year Limited Warranty On Tank And Parts • 1-Year Labour Warranty

- Glass-lined steel tank with anode rod for corrosion protection
- Two, Zinc-coated, Copper heating elements
- 2" Energy-Efficient, CFC-free foam insulation
- Factory installed temperature / pressure relief valve

ITEM NUMBER	TANK CAPACITY		WATTAGE AT 240 VOLTS	MINIMUM FUSE REQUIRED	MINIMUM WIRE SIZE	U.S. GAL./HR. RECOVERY @ 90°F RISE		DIMENSIONS IN INCHES		INSULATION R-FACTOR
	LITRES	IMPERIAL GALLON				LITRES PER HOUR	IMPERIAL GALLON PER HOUR	DIAMETER	HEIGHT	
73402	170	37.5	3000	15 amp	14 ga.	51.7	11.4	22"	48"	R-16
73403	273	60.0	4500	30 amp	10 ga.	77.6	17.1	24"	60.5"	R-16
73404	187	41.2	3000	15 amp	14 ga.	51.7	11.4	20.5"	60.25"	R-16

GOOD

KENMORE COMPACT AND POINT-OF-USE Electric Water Heaters 6-Year Limited Warranty On Tank And Parts • 1-Year Labour Warranty

- Glass-lined steel tank with anode rod for corrosion protection
- Zinc-coated, Copper heating elements
- Energy-Efficient, CFC-free foam insulation
- Factory installed temperature / pressure relief valve

ITEM NUMBER	TANK CAPACITY		ELEMENT WATTAGE		MINIMUM FUSE REQUIRED	MINIMUM WIRE SIZE	U.S. GAL./HR. RECOVERY @ 90°F RISE		DIMENSIONS IN INCHES	
	LITRES	IMPERIAL GALLON	120 VOLTS	240 VOLTS			LITRES PER HOUR	IMPERIAL GALLON PER HOUR	DIAMETER	HEIGHT
73772	34	7.5	1500		15 amp	14 ga.	25.9	5.7	16"	18.25"
73773	67	14.8	1500		15 amp	14 ga.	25.9	5.7	19"	25.25"
73443	102	22.5		3000	15 amp	14 ga.	51.7	11.4	22"	30"
73771*	9.5	2.0	1500		15 amp	14 ga.	25.9	5.7	11" x 14" x 16"	

* Item 73771, Point of Use water heater, has 6-year warranty on tank and 1-year warranty on parts. Dimensions and product specifications are subject to change without notice. All models shown comply with the latest efficiency requirements of NRCAN.